

SAFETY DATA SHEET



ROYCO LANDING GEAR FLUID YELLOW

Version 1.9 Revision Date: 03/26/2020 SDS Number: 400000001798 Date of last issue: 02/04/2020
Date of first issue: 12/05/2014

SECTION 1. IDENTIFICATION

Product name: ROYCO LANDING GEAR FLUID YELLOW
LANDING GEAR FLUID

Product Use Description: Lubricant

Synonyms: Synthetic Lubricant Formulation

Company: Manufacturer
Anderol Specialty Lubricants, a division of Lanxess Solutions US Inc.
215 Merry Lane
East Hanover, NJ
07936
United States of America (USA)
Telephone: +1 203-573-4596, Toll Free: +1 888-263-3765

Emergency telephone number: CHEMTREC
(24 hours) 800-424-9300

For additional emergency telephone numbers see section 16 of the Safety Data Sheet.

Prepared by: Product Safety Department
(US) +1 866-430-2775

MSDSRequest@lanxess.com

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin irritation : Category 2

Eye irritation : Category 2A

Aspiration hazard : Category 1

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 2

GHS label elements

ROYCO LANDING GEAR FLUID YELLOW

Version 1.9 Revision Date: 03/26/2020 SDS Number: 400000001798 Date of last issue: 02/04/2020
 Date of first issue: 12/05/2014

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

:

Prevention:P264 Wash skin thoroughly after handling.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.**Response:**P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.
 P391 Collect spillage.**Storage:**

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 50 - < 70
Distillates (petroleum), hydrotreated middle	64742-46-7	>= 10 - < 20
Distillates (petroleum), hydrotreated light	64742-47-8	>= 5 - < 10
Phosphorodithioic acid, mixed O,O-bis(iso-	68457-79-4	>= 1 - < 5

SAFETY DATA SHEET



ROYCO LANDING GEAR FLUID YELLOW

Version 1.9 Revision Date: 03/26/2020 SDS Number: 400000001798 Date of last issue: 02/04/2020
Date of first issue: 12/05/2014

Bu and pentyl) esters, zinc salts		
Phenol, isobutylated, phosphate [Tri-phenyl phosphate > 25%]	68937-40-6	>= 0.1 - < 1
2,6-di-tert-butyl-p-cresol	128-37-0	>= 0.1 - < 1

Actual concentration is withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

- If inhaled : If inhaled
Move to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
In case of bluish discoloration (lips, ear lobes, fingernails), give oxygen as quickly as possible.
If symptoms persist, call a physician.
- In case of skin contact : In case of skin contact
Wash off with soap and water.
Remove contaminated clothing and shoes.
Wash contaminated clothing before re-use.
Get medical attention if irritation develops and persists.
- In case of eye contact : In case of eye contact
Rinse thoroughly with plenty of water, also under the eyelids.
If eye irritation persists, consult a specialist.
- If swallowed : If swallowed, DO NOT induce vomiting.
Consult a physician if necessary.
- Most important symptoms and effects, both acute and delayed : Aspiration may cause pulmonary oedema and pneumonitis.
No information available.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- Notes to physician : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO2)
Dry powder
Foam
Alcohol-resistant foam
Water mist
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Burning produces noxious and toxic fumes.

ROYCO LANDING GEAR FLUID YELLOW

Version 1.9 Revision Date: 03/26/2020 SDS Number: 400000001798 Date of last issue: 02/04/2020
 Date of first issue: 12/05/2014

Further information : In the event of fire, cool tanks with water spray.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation. Forms slippery/greasy layers with water.

Environmental precautions : Should not be released into the environment. Do not contaminate water. Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice. Keep container closed when not in use. Do not use pressure to empty drums. Ensure all equipment is electrically grounded before beginning transfer operations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

Further information on storage stability : Stable under recommended storage conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
triphenyl phosphate	115-86-6	TWA	3 mg/m ³	ACGIH
		TWA	3 mg/m ³	OSHA Z-1
		TWA	3 mg/m ³	OSHA P0
		TWA	3 mg/m ³	NIOSH REL
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH

SAFETY DATA SHEET



ROYCO LANDING GEAR FLUID YELLOW

Version 1.9 Revision Date: 03/26/2020 SDS Number: 400000001798 Date of last issue: 02/04/2020
 Date of first issue: 12/05/2014

		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
		TWA (Mist)	5 mg/m ³	OSHA P0
Distillates (petroleum), hydrotreated middle	64742-46-7	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
		TWA (Mist)	5 mg/m ³	OSHA P0
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
		TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Mist)	5 mg/m ³	OSHA P0
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
2,6-di-tert-butyl-p-cresol	128-37-0	TWA	10 mg/m ³	OSHA P0
		TWA (Inhalable fraction and vapor)	2 mg/m ³	ACGIH
		TWA	10 mg/m ³	NIOSH REL

Personal protective equipment

Respiratory protection : Breathing apparatus needed only when aerosol or mist is formed.
 In the case of vapour formation use a respirator with an approved filter.

Hand protection

Remarks : Neoprene gloves

Eye protection : Safety glasses with side-shields
 Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Hygiene measures : Avoid contact with skin, eyes and clothing.
 Provide adequate ventilation.
 Do not breathe dust or spray mist.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : yellow

SAFETY DATA SHEET



ROYCO LANDING GEAR FLUID YELLOW

Version 1.9 Revision Date: 03/26/2020 SDS Number: 400000001798 Date of last issue: 02/04/2020
Date of first issue: 12/05/2014

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/range : Not applicable

Boiling point/boiling range : No data available

Flash point : 232 °F / 111 °C

Evaporation rate : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.8698 g/cm³

Solubility(ies)

 Water solubility : slightly soluble

 Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Self-Accelerating decomposition temperature (SADT) : Method: No information available.

Viscosity

 Viscosity, kinematic : 14.55 mm²/s (104 °F / 40 °C)

Oxidizing potential : No information available.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under normal conditions.

ROYCO LANDING GEAR FLUID YELLOW

Version 1.9 Revision Date: 03/26/2020 SDS Number: 400000001798 Date of last issue: 02/04/2020
Date of first issue: 12/05/2014

Possibility of hazardous reactions : Hazardous polymerisation does not occur.

Conditions to avoid : Heat

Incompatible materials : Strong acids and strong bases

Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Eye contact
Skin contact

Acute toxicity**Product:**

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 31.44 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:**Distillates (petroleum), hydrotreated light naphthenic:**

Acute oral toxicity : LD50 Oral: > 5,000 mg/kg

Distillates (petroleum), hydrotreated middle:

Acute inhalation toxicity : LC50: 4.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Acute oral toxicity : LD50 Oral (Rat): > 3,600 mg/kg

Phenol, isobutyleneated, phosphate [Triphenyl phosphate > 25%]:

Acute inhalation toxicity : LC50 (Rat): > 0.4 mg/l
Exposure time: 6 h
Test atmosphere: vapour
Symptoms: No adverse effects
GLP: no
Assessment: The substance or mixture has no acute inhalation toxicity

2,6-di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat, male and female): > 2,930 mg/kg

ROYCO LANDING GEAR FLUID YELLOW

Version 1.9 Revision Date: 03/26/2020 SDS Number: 400000001798 Date of last issue: 02/04/2020
Date of first issue: 12/05/2014

Method: OECD Test Guideline 401

GLP: yes

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation**Components:****Distillates (petroleum), hydrotreated middle:**

Species : Rabbit
Result : irritating

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Species : Rabbit
Result : Irritating to skin.

2,6-di-tert-butyl-p-cresol:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation**Components:****Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:**

Species : Rabbit
Result : Risk of serious damage to eyes.

2,6-di-tert-butyl-p-cresol:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation**Components:****2,6-di-tert-butyl-p-cresol:**

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity**Components:****2,6-di-tert-butyl-p-cresol:**

Genotoxicity in vitro : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Result: negative

ROYCO LANDING GEAR FLUID YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 02/04/2020
1.9	03/26/2020	400000001798	Date of first issue: 12/05/2014

Test Type: Chromosome aberration test in vitro
 Metabolic activation: with and without metabolic activation
 Result: negative

Test Type: unscheduled DNA synthesis assay
 Result: negative

Test Type: In vitro mammalian cell gene mutation test
 Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test
 Species: Mouse (male and female)
 Cell type: Bone marrow
 Method: Mutagenicity (micronucleus test)
 Result: negative

Test Type: in vivo assay
 Species: Rat (male)
 Cell type: Bone marrow
 Application Route: Oral
 Method: Mutagenicity (in vivo mammalian bone-marrow cyto-genetic test, chromosomal analysis)
 Result: negative

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

Carcinogenicity

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Components:****2,6-di-tert-butyl-p-cresol:**

Reproductive toxicity - Assessment : No toxicity to reproduction
 No effects on or via lactation

STOT - repeated exposure**Components:****2,6-di-tert-butyl-p-cresol:**

Exposure routes : Oral
 Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

ROYCO LANDING GEAR FLUID YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 02/04/2020
1.9	03/26/2020	400000001798	Date of first issue: 12/05/2014

Aspiration toxicity**Components:****Distillates (petroleum), hydrotreated light naphthenic:**

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks : There is no data available for this product.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**Toxicity to fish :
Remarks: No data availableToxicity to daphnia and other :
aquatic invertebrates Remarks: No data availableToxicity to algae :
Remarks: No data available**Components:****Distillates (petroleum), hydrotreated middle:**Toxicity to fish : LL50: 1.13 mg/l
Exposure time: 96 h
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.Toxicity to daphnia and other : EL50: 7.385 mg/l
aquatic invertebrates Exposure time: 48 h
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.Toxicity to algae : EL50: 1.714 mg/l
Exposure time: 72 hToxicity to fish (Chronic tox- : NOELR (Oncorhynchus mykiss (rainbow trout)): 0.069 mg/l
icity) Exposure time: 14 d
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

Toxicity to daphnia and other : NOELR (Daphnia magna (Water flea)): 0.163 mg/l

ROYCO LANDING GEAR FLUID YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 02/04/2020
1.9	03/26/2020	400000001798	Date of first issue: 12/05/2014

aquatic invertebrates (Chronic toxicity)

Exposure time: 21 d
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 23 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae : EL50 (Desmodesmus subspicatus (green algae)): 24 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.4 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
GLP: yes

Phenol, isobutyleneated, phosphate [Triphenyl phosphate > 25%]:

Toxicity to fish : LC50 (Fish): 0.8 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.202 mg/l
Exposure time: 48 h

Toxicity to fish (Chronic toxicity) : NOEC: 0.093 mg/l
Exposure time: 90 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.0399 mg/l
Exposure time: 21 d

Persistence and degradability**Components:****Distillates (petroleum), hydrotreated middle:**

Biodegradability : Remarks: Readily biodegradable.

Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts:

Biodegradability : Result: Not readily biodegradable.

ROYCO LANDING GEAR FLUID YELLOW

Version 1.9 Revision Date: 03/26/2020 SDS Number: 400000001798 Date of last issue: 02/04/2020
Date of first issue: 12/05/2014

Biodegradation: 1.5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Phenol, isobutylated, phosphate [Triphenyl phosphate > 25%]:

Biodegradability : GLP: yes
Remarks: Readily biodegradable.

2,6-di-tert-butyl-p-cresol:

Biodegradability : aerobic
Inoculum: activated sludge
Concentration: 50 mg/l
Result: According to the results of tests of biodegradability this product is not readily biodegradable.
Biodegradation: 4.5 %
Exposure time: 28 d

Bioaccumulative potential**Product:**

Bioaccumulation : Remarks: No data available

Components:**Phenol, isobutylated, phosphate [Triphenyl phosphate > 25%]:**

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): 1,850

Partition coefficient: n-octanol/water : log Pow: 4.68 (77 °F / 25 °C)

2,6-di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 230 - 2,500
Exposure time: 56 d
Temperature: 77 °F / 25 °C
Concentration: 0.05 mg/l

Partition coefficient: n-octanol/water : log Pow: 5.1
GLP: yes

log Pow: 4.2

Mobility in soil**Product:**

Mobility : Remarks: No data available

Other adverse effects**Product:**

ROYCO LANDING GEAR FLUID YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 02/04/2020
1.9	03/26/2020	400000001798	Date of first issue: 12/05/2014

Results of PBT and vPvB assessment : This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : There is no data available for this product.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Distillates (petroleum), hydrotreated middle, Phenol, isobutyleneated, phosphate [Triphenyl phosphate > 25%])

Class : 9

Packing group : III

Labels : Miscellaneous

Environmentally hazardous : yes

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Distillates (petroleum), hydrotreated middle, Phenol, isobutyleneated, phosphate [Triphenyl phosphate > 25%])

Class : 9

Packing group : III

Labels : 9

EmS Code : F-A, S-F

Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ROYCO LANDING GEAR FLUID YELLOW

Version 1.9 Revision Date: 03/26/2020 SDS Number: 400000001798 Date of last issue: 02/04/2020
Date of first issue: 12/05/2014

49 CFR

UN/ID/NA number : UN 3082
 Proper shipping name : Environmentally hazardous substances, liquid, n.o.s.
 (Distillates (petroleum), hydrotreated middle, Phenol, isobu-
 tylenated, phosphate [Triphenyl phosphate > 25%])
 Class : 9
 Packing group : III
 Labels : CLASS 9
 ERG Code : 171
 Marine pollutant : yes(Distillates (petroleum), hydrotreated middle, Phenol, iso-
 butylenated, phosphate [Triphenyl phosphate > 25%])
 Remarks : Shipment by ground under DOT is non-regulated; however it
 may be shipped per the applicable hazard classification to
 facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantities**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
2-methylpropan-1-ol	78-83-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantities

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantities

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Skin corrosion or irritation
 Serious eye damage or eye irritation
 Aspiration hazard

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Phosphorodithioic acid, 68457-79-4 >= 1 - < 5 %
 mixed O,O-bis(iso-Bu
 and pentyl) esters, zinc
 salts

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

ROYCO LANDING GEAR FLUID YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 02/04/2020
1.9	03/26/2020	400000001798	Date of first issue: 12/05/2014

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

1-phenylazo-2-naphthol 842-07-9

Washington Chemicals of High Concern

1-phenylazo-2-naphthol 842-07-9

California Prop. 65

WARNING: This product can expose you to chemicals including 1-phenylazo-2-naphthol, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated middle	64742-46-7
Distillates (petroleum), hydrotreated light	64742-47-8
Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated middle	64742-46-7
Distillates (petroleum), hydrotreated light	64742-47-8

Please note that Section 3 of this document lists only the hazardous components required by the specific country or region hazard communication regulations. The chemical identifiers listed in Section 3 are used globally for hazard communication purposes and may not reflect those used for chemical inventory coverage in a particular country or region. The chemical inventory information given in Section 15 of this document applies to the product as a whole and should be used when evaluating inventory compliance.

The components of this product are reported in the following inventories:

TCSI	: On the inventory, or in compliance with the inventory
US.TSCA	: All substances listed as active on the TSCA inventory
AICS	: On the inventory, or in compliance with the inventory
DSL	: All components of this product are on the Canadian DSL
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

SAFETY DATA SHEET



ROYCO LANDING GEAR FLUID YELLOW

Version	Revision Date:	SDS Number:	Date of last issue: 02/04/2020
1.9	03/26/2020	400000001798	Date of first issue: 12/05/2014

ment; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/26/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN