



Revision Number: 002.1

Issue date: 08/06/2018

**1. PRODUCT AND COMPANY IDENTIFICATION**

|                               |  |                     |               |
|-------------------------------|--|---------------------|---------------|
| <b>Product name:</b>          | <b>LOCTITE EA 9891RP AERO PART A QT</b>        | <b>IDH number:</b>  | 944960        |
| <b>Product type:</b>          | Adhesive for the Aerospace Industry            | <b>Item number:</b> | AA9340016     |
| <b>Restriction of Use:</b>    | None identified                                | <b>Region:</b>      | United States |
| <b>Company address:</b>       | <b>Contact information:</b>                    |                     |               |
| Henkel Corporation            | Telephone: +1 (860) 571-5100                   |                     |               |
| One Henkel Way                | MEDICAL EMERGENCY Phone: Poison Control Center |                     |               |
| Rocky Hill, Connecticut 06067 | 1-877-671-4608 (toll free) or 1-303-592-1711   |                     |               |
|                               | TRANSPORT EMERGENCY Phone: CHEMTREC            |                     |               |
|                               | 1-800-424-9300 (toll free) or 1-703-527-3887   |                     |               |
|                               | Internet: www.henkelna.com                     |                     |               |

**2. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

**WARNING:** CAUSES SKIN IRRITATION.  
MAY CAUSE AN ALLERGIC SKIN REACTION.  
CAUSES SERIOUS EYE IRRITATION.

| HAZARD CLASS       | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN IRRITATION    | 2               |
| EYE IRRITATION     | 2A              |
| SKIN SENSITIZATION | 1               |

**PICTOGRAM(S)****Precautionary Statements**

|                    |  |
|--------------------|--|
| <b>Prevention:</b> | Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.   |
| <b>Response:</b>   | IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. |
| <b>Storage:</b>    | Not prescribed   |
| <b>Disposal:</b>   | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.  |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

| Hazardous Component(s) | CAS Number  | Percentage* |
|------------------------|-------------|-------------|
| Epoxy resin            | Proprietary | 70 - 80     |
| Modified epoxy resin   | Unknown     | 10 - 20     |
| Titanium dioxide       | 13463-67-7  | 0.1 - 1     |
| Carbon black           | 1333-86-4   | 0.1 - 1     |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

|                            |  |
|----------------------------|--|
| <b>Inhalation:</b>         | If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.                                 |
| <b>Skin contact:</b>       | Remove contaminated clothing and footwear. Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention. |
| <b>Eye contact:</b>        | In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.                           |
| <b>Ingestion:</b>          | Get immediate medical attention. Do not induce vomiting.   |
| <b>Symptoms:</b>           | See Section 11.  |
| <b>Notes to physician:</b> | Treat symptomatically and supportively.  |

## 5. FIRE FIGHTING MEASURES

|   |  |
|---|--|
| <b>Extinguishing media:</b>               | Water spray (fog), foam, dry chemical or carbon dioxide.   |
| <b>Special firefighting procedures:</b>   | Wear full protective clothing. Wear self-contained breathing apparatus.  |
| <b>Unusual fire or explosion hazards:</b> | May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.                             |
| <b>Hazardous combustion products:</b>     | Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen. |

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |   |
|-----------------------------------|---|
| <b>Environmental precautions:</b> | Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways. |
| <b>Clean-up methods:</b>          | Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.                         |

## 7. HANDLING AND STORAGE

**Handling:**

For the Part A plus Part B adhesive mixture, follow curing schedule as recommended in product literature. Do not heat Part A at temperatures greater than 100 °C (212 °F). This material may self-react at higher temperatures and cause an exotherm. The exotherm has the potential for release of excessive energy and toxic gasses. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full.

**Storage:**

For safe storage, store at or below 29 °C (84.2 °F)  
Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV                       | OSHA PEL  | AIHA WEEL | OTHER |
|------------------------|---------------------------------|---|-----------|-------|
| Epoxy resin            | None                            | None  | None      | None  |
| Modified epoxy resin   | None                            | None  | None      | None  |
| Titanium dioxide       | 10 mg/m3 TWA                    | 15 mg/m3 PEL Total dust.<br>15 MPPCF TWA Respirable fraction.<br>15 mg/m3 TWA Total dust.<br>50 MPPCF TWA Total dust.<br>5 mg/m3 TWA Respirable fraction. | None      | None  |
| Carbon black           | 3 mg/m3 TWA Inhalable fraction. | 3.5 mg/m3 PEL   | None      | None  |

**Engineering controls:**

Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

**Respiratory protection:**

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.

**Eye/face protection:**

Safety goggles or safety glasses with side shields.

**Skin protection:**

Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                     |                      |
|-------------------------------------|----------------------|
| Physical state:                     | Solid                |
| Color:                              | Black                |
| Odor:                               | Epoxy                |
| Odor threshold:                     | Not available.       |
| pH:                                 | Not available.       |
| Vapor pressure:                     | Nil                  |
| Boiling point/range:                | Not determined       |
| Melting point/ range:               | Not applicable       |
| Specific gravity:                   | 1.03                 |
| Vapor density:                      | > 1                  |
| Flash point:                        | > 93 °C (> 199.4 °F) |
| Flammable/Explosive limits - lower: | Not available.       |
| Flammable/Explosive limits - upper: | Not available.       |
| Autoignition temperature:           | Not applicable       |

|   |   |
|---|---|
| <b>Flammability:</b>                            | Not applicable  |
| <b>Evaporation rate:</b>                        | Not determined  |
| <b>Solubility in water:</b>                     | Negligible  |
| <b>Partition coefficient (n-octanol/water):</b> | Not determined  |
| <b>VOC content:</b>                             | < 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated) |
| <b>Viscosity:</b>                               | Not available.  |
| <b>Decomposition temperature:</b>               | Not available.  |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Stability:</b>                        | Stable at normal conditions.   |
| <b>Hazardous reactions:</b>              | May occur.   |
| <b>Hazardous decomposition products:</b> | Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.   |
| <b>Incompatible materials:</b>           | Keep away from strong oxidizing agents, strong Lewis or mineral acids.   |
| <b>Reactivity:</b>                       | Not available.   |
| <b>Conditions to avoid:</b>              | Do not mix in batches greater than 200 grams (0.44 pounds) unless you plan to use immediately. Do not heat mixed adhesive unless curing surfaces to be bonded. Failure to observe these precautions may result in excessive heat build-up causing an exotherm. The exotherm has the potential for release of toxic gasses. |

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

|                      |  |
|----------------------|--|
| <b>Inhalation:</b>   | May cause respiratory tract irritation.  |
| <b>Skin contact:</b> | This product may cause irritation to the skin. This product may cause an allergic skin reaction. |
| <b>Eye contact:</b>  | This product may cause irritation to the eyes.   |
| <b>Ingestion:</b>    | Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.                  |

| Hazardous Component(s) | LD50s and LC50s                 | Immediate and Delayed Health Effects                    |
|------------------------|---------------------------------|---|
| Epoxy resin            | None                            | Allergen, Irritant                                      |
| Modified epoxy resin   | None                            | No Data   |
| Titanium dioxide       | None                            | Irritant, Respiratory, Some evidence of carcinogenicity |
| Carbon black           | Oral LD50 (Rat) = > 8,000 mg/kg | Respiratory, Some evidence of carcinogenicity           |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen<br>(Specifically Regulated) |
|------------------------|----------------|-----------------|---|
| Epoxy resin            | No             | No              | No  |
| Modified epoxy resin   | No             | No              | No  |
| Titanium dioxide       | No             | Group 2B        | No  |
| Carbon black           | No             | Group 2B        | No  |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Toxic to aquatic organisms

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:** Material, if discarded, is not expected to be a characteristic hazardous waste under RCRA.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

#### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Environmentally hazardous substance, solid, n.o.s. (Bisphenol-A Epichlorhydrin resin)  
**Hazard class or division:** 9  
**Identification number:** UN 3077  
**Packing group:** III

#### Water Transportation (IMO/IMDG)

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Bisphenol-A Epichlorhydrin resin)  
**Hazard class or division:** 9  
**Identification number:** UN 3077  
**Packing group:** III  
**Marine pollutant:** Bisphenol-A Epichlorhydrin resin  
**Exceptions:** Classified per IMDG Amendment 34; Effective Jan 1, 2010.

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health  
**CERCLA/SARA Section 313:** None above reporting de minimis.

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

#### Canada Regulatory Information

**CEPA DSL/NDL Status:** One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.



Revision Number: 002.8

Issue date: 12/27/2016

## 1. PRODUCT AND COMPANY IDENTIFICATION

|                               |  |                     |               |
|-------------------------------|--|---------------------|---------------|
| <b>Product name:</b>          | <b>LOCTITE EA 9891RP AERO PART B PT</b>        | <b>IDH number:</b>  | 944971        |
| <b>Product type:</b>          | Adhesive for the Aerospace Industry            | <b>Item number:</b> | AB9340015     |
| <b>Restriction of Use:</b>    | None identified                                | <b>Region:</b>      | United States |
| <b>Company address:</b>       | <b>Contact information:</b>                    |                     |               |
| Henkel Corporation            | Telephone: +1 (860) 571-5100                   |                     |               |
| One Henkel Way                | MEDICAL EMERGENCY Phone: Poison Control Center |                     |               |
| Rocky Hill, Connecticut 06067 | 1-877-671-4608 (toll free) or 1-303-592-1711   |                     |               |
|                               | TRANSPORT EMERGENCY Phone: CHEMTREC            |                     |               |
|                               | 1-800-424-9300 (toll free) or 1-703-527-3887   |                     |               |
|                               | Internet: www.henkelna.com                     |                     |               |

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** HARMFUL IF SWALLOWED.  
CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.  
MAY CAUSE AN ALLERGIC SKIN REACTION.

| HAZARD CLASS        | HAZARD CATEGORY |
|---------------------|-----------------|
| ACUTE TOXICITY ORAL | 4               |
| SKIN CORROSION      | 1B              |
| SERIOUS EYE DAMAGE  | 1               |
| SKIN SENSITIZATION  | 1               |

### PICTOGRAM(S)



### Precautionary Statements

|                    |   |
|--------------------|---|
| <b>Prevention:</b> | Do not breathe dust or fumes. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.   |
| <b>Response:</b>   | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse. |
| <b>Storage:</b>    | Store locked up.  |
| <b>Disposal:</b>   | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.   |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)      | CAS Number | Percentage* |
|-----------------------------|------------|-------------|
| 4-Tert-butylphenol          | 98-54-4    | 30 - 40     |
| Trimethylhexane-1,6-diamine | 25620-58-0 | 10 - 20     |
| m-Phenylenebis(methylamine) | 1477-55-0  | 10 - 20     |
| Silicon dioxide             | 7631-86-9  | 10 - 20     |
| 4-Nonylphenol, branched     | 84852-15-3 | 1 - 5       |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### 4. FIRST AID MEASURES

|                            |  |
|----------------------------|--|
| <b>Inhalation:</b>         | If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.                                 |
| <b>Skin contact:</b>       | Remove contaminated clothing and footwear. Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention. |
| <b>Eye contact:</b>        | In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.                           |
| <b>Ingestion:</b>          | Get immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.  |
| <b>Symptoms:</b>           | See Section 11.  |
| <b>Notes to physician:</b> | Treat symptomatically and supportively.  |

### 5. FIRE FIGHTING MEASURES

|   |   |
|---|---|
| <b>Extinguishing media:</b>               | Water spray (fog), foam, dry chemical or carbon dioxide.  |
| <b>Special firefighting procedures:</b>   | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Cartridge respirators do not provide adequate protection for fire fighters or exotherm mitigation. |
| <b>Unusual fire or explosion hazards:</b> | May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.  |
| <b>Hazardous combustion products:</b>     | Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.  |

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |   |
|-----------------------------------|---|
| <b>Environmental precautions:</b> | Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways. |
| <b>Clean-up methods:</b>          | Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.                         |

## 7. HANDLING AND STORAGE

### Handling:

Avoid contact with eyes, skin and clothing. For the Part A plus Part B adhesive mixture, follow curing schedule as recommended in product literature. Do not heat Part B at temperatures greater than 100 °C (212 °F). This material may self-react at higher temperatures and cause an exotherm. The exotherm has the potential for release of excessive energy and toxic gasses. Empty containers retain product residue, so obey hazard warnings and handle empty containers as if they were full. Do not cut, grind, weld, or drill on or near this container.

### Storage:

For safe storage, store at or below 29 °C (84.2 °F)  
Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)      | ACGIH TLV                | OSHA PEL                      | AIHA WEEL | OTHER                               |
|-----------------------------|--------------------------|-------------------------------|-----------|-------------------------------------|
| 4-Tert-butylphenol          | None                     | None                          | None      | None                                |
| Trimethylhexane-1,6-diamine | None                     | None                          | None      | None                                |
| m-Phenylenebis(methylamine) | 0.1 mg/m3 Ceiling (SKIN) | None                          | None      | None                                |
| Silicon dioxide             | 6 mg/m3 TWA              | 20 MPPCF TWA<br>0.8 mg/m3 TWA | None      | 3 mg/m3 TWA<br>Respirable fraction. |
| 4-Nonylphenol, branched     | None                     | None                          | None      | None                                |

### Engineering controls:

Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.

### Respiratory protection:

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.

### Eye/face protection:

Safety goggles or safety glasses with side shields.

### Skin protection:

Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|  |   |
|--|---|
| Physical state:                          | Solid   |
| Color:                                   | White   |
| Odor:                                    | Ammoniacal  |
| Odor threshold:                          | Not available.  |
| pH:                                      | Not determined  |
| Vapor pressure:                          | Not determined  |
| Boiling point/range:                     | Not determined  |
| Melting point/ range:                    | Not determined  |
| Specific gravity:                        | 0.5   |
| Vapor density:                           | Not determined  |
| Flash point:                             | > 93 °C (> 199.4 °F)  |
| Flammable/Explosive limits - lower:      | Not determined  |
| Flammable/Explosive limits - upper:      | Not determined  |
| Autoignition temperature:                | Not applicable  |
| Flammability:                            | Not applicable  |
| Evaporation rate:                        | Not determined  |
| Solubility in water:                     | Negligible  |
| Partition coefficient (n-octanol/water): | Not determined  |
| VOC content:                             | < 10 g/l per SCAQMD Rule 1124 [EPA Test Method 24/304-91] (estimated) |



Viscosity: Not available.  
Decomposition temperature: Not available.

## 10. STABILITY AND REACTIVITY

**Stability:** Stable at normal conditions.

**Hazardous reactions:** May occur.

**Hazardous decomposition products:** Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.

**Incompatible materials:** Keep away from strong oxidizing agents, strong Lewis or mineral acids.

**Reactivity:** Not available.

**Conditions to avoid:** Do not mix in batches greater than 200 grams (0.44 pounds) unless you plan to use immediately. Do not heat mixed adhesive unless curing surfaces to be bonded. Failure to observe these precautions may result in excessive heat build-up causing an exotherm.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

**Inhalation:** Inhalation of dusts of this product may cause severe irritation and burns to the respiratory tract.

**Skin contact:** This product is severely irritating to the skin and may cause burns. May cause allergic skin reaction. May be harmful if absorbed through skin.

**Eye contact:** This product is severely irritating to the eyes and may cause irreversible damage including burns and blindness.

**Ingestion:** Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract. May be harmful if swallowed.

| Hazardous Component(s)      | LD50s and LC50s  | Immediate and Delayed Health Effects |
|-----------------------------|--|--------------------------------------|
| 4-Tert-butylphenol          | None   | Irritant, Allergen, Skin, Corrosive  |
| Trimethylhexane-1,6-diamine | None   | Allergen                             |
| m-Phenylenebis(methylamine) | None   | Irritant, Liver, Kidney, Corrosive   |
| Silicon dioxide             | Oral LD50 (Rat) = > 22,500 mg/kg<br>Oral LD50 (Mouse) = > 15,000 mg/kg | Nuisance dust                        |
| 4-Nonylphenol, branched     | None   | Irritant, Corrosive                  |

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:** This product, if discarded, may be characterized as a RCRA corrosive waste, D002. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Corrosive solids, n.o.s. (m-Xylylenediamine, Nonylphenol)  
**Hazard class or division:** 8  
**Identification number:** UN 1759  
**Packing group:** II  
**Marine pollutant:** Nonylphenol

#### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Corrosive solid, n.o.s. (m-Xylylenediamine, Nonylphenol)  
**Hazard class or division:** 8  
**Identification number:** UN 1759  
**Packing group:** II

#### Water Transportation (IMO/IMDG)

**Proper shipping name:** CORROSIVE SOLID, N.O.S. (m-Xylylenediamine, Nonylphenol)  
**Hazard class or division:** 8  
**Identification number:** UN 1759  
**Packing group:** II  
**Marine pollutant:** Nonylphenol

### 15. REGULATORY INFORMATION

#### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12 (b) Export Notification:** Alkyl phenol (CAS# 84852-15-3).

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health  
**CERCLA/SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). 4-Nonylphenol, branched (CAS# 84852-15-3).

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer.

#### Canada Regulatory Information

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

**Prepared by:** Mark Mau, Regulatory Affairs Specialist

**Issue date:** 12/27/2016

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ( Henkel ) does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user s responsibility to determine the suitability of Henkel s products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel s products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel s products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

**Prepared by:** Regulatory Affairs

**Issue date:** 08/06/2018

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.