



## Part Reference Guide

# DR5875

### Applications

| Manufacturer | Model | Series | Position |
|--------------|-------|--------|----------|
| Agusta Bell  |       | AB 139 | Aux      |

### Technical Data

| Ply Rating | Speed Rating (MPH) | Max Load (lbs) | Tubed/Tubeless | Chined |
|------------|--------------------|----------------|----------------|--------|
| 10         | 120                | 2150           | Tubed          | No     |

### Inflation & Dimensions

|                                 |        |
|---------------------------------|--------|
| Size                            | 5.00-5 |
| Inflation Pressure Unloaded PSI | 88     |
| Inflation Pressure Loaded PSI   | 92     |
| Inf Dim Width Shoulder          | 4.20   |
| Inf Dim Width Max               | 4.95   |
| Inf Dim Width Min               | 4.65   |
| Inf Dim OD Min                  | 13.65  |
| Inf Dim OD Max                  | 14.20  |
| Inf Dim OD Shoulder             | 12.55  |
| Rim Dim Width Between Flanges   | 3.50   |
| Rim Dim Ledge Diameter          | 5      |
| Rim Dim Flange Height           | 0.75   |
| Rim Dim Min Ledge Width         | 1.25   |

### Approvals

|                   |                                      |
|-------------------|--------------------------------------|
| QTR Number        | 1455                                 |
| Test Spec         | TSO-C62d                             |
| CAA EASA Approval | E15817 13/04/2000                    |
| FAA Approval      | SH/VK/11/06/00:0377:00<br>06/11/2000 |
| MOD Approval      | DR5875                               |
| NSN Approval      | Not Declared                         |
| Civilian/Military | Civilian                             |