

# Interlok® and Monobolt®

## Breakstem Riveting System



Interlok® and Monobolt® multi-grip structural breakstem fasteners provide a fully sealed joint and lock. With exceptional shear strength and clamp load Interlok®/Monobolt® is designed to deliver the high strength performance required in structural applications.



| Huck Magna-Lok Part Number | SEF Interlok® Part Number | SEF Monobolt® Part Number * | Interlok® Best MOQ and Lead Time | Monobolt® Best MOQ and Lead Time |
|----------------------------|---------------------------|-----------------------------|----------------------------------|----------------------------------|
| MGLP-B6-4                  | BAPI-06-04                | BAPV-06-04                  | 50K - 10 wks                     | 100K - 14 wks                    |
| MGLP-B6-7                  | BAPI-06-07                | BAPV-E06-07                 | 100K - 14 wks                    | 100K - 14 wks                    |
| MGLP-B6-E                  | BAPI-E06-07               | BAPV-E06-07                 | 100K - 14 wks                    | 100K - 14 wks                    |
| MGLP-B8-6                  | BAPI-08-06                | BAPV-08-06                  | 50K - 8 wks                      | 50K - 14 wks                     |
| MGLP-B8-10                 | BAPI-08-10                | BAPV-E08-10                 | 60K - 10 wks                     | 100K - 14 wks                    |
| MGLP-B8-E                  | BAPI-E08-10               | BAPV-E08-10                 | 60K - 10 wks                     | 100K - 14 wks                    |
| MGLP-R6-4                  | SSPI-06-04                | SSPV-06-04                  | 50K - 8 wks                      | 100K - 8 wks                     |
| MGLP-R6-7                  | SSPI-06-07                | SSPV-E06-07                 | 100K - 8 wks                     | 100K - 10 wks                    |
| MGLP-R6-10                 | SSPI-06-10                | N/A                         | 100K - 16 wks                    | N/A                              |
| MGLP-R6-E                  | SSPI-E06-07               | SSPV-E06-07                 | 50K - 10 wks                     | 100K - 10 wks                    |
| MGLP-R8-6                  | SSPI-08-06                | SSPV-08-06                  | 50K - 8 wks                      | 50K - 10 wks                     |
| MGLP-R8-10                 | SSPI-08-10                | SSPV-E08-10                 | 50K - 10 wks                     | 50K - 10 wks                     |
| MGLP-R8-E                  | SSPI-E08-10               | SSPV-E08-10                 | 50K - 8 wks                      | 50K - 10 wks                     |
| MGLP-R12-12                | SSPI-12-10                | 02771-01228                 | 50K - 18 wks                     | 50K - 18 wks                     |
| MGLP-U8-6                  | CCPI-08-06                | CCPV-08-06                  | 50K - 16 wks                     | 50K - 16 wks                     |
| MGLP-U8-10                 | CCPI-08-10                | CCPV-E08-10                 | 50K - 18 wks                     | 50K - 18 wks                     |
| MGLP-U8-E                  | CCPI-E08-10               | CCPV-E08-10                 | 50K - 18 wks                     | 50K - 18 wks                     |
| MGL100-B6-6                | BACI-06-06                | BACV-06-06                  | 100K - 16 wks                    | 100K - 16wks                     |
| MGL100-R6-6                | SSCI-06-06                | SSCV-06-06                  | 100K - 8 wks                     | 100K - 14 wks                    |
| MGL100-R8-8                | SSCI-08-08                | SSCV-08-08                  | 80K - 14 wks                     | 80K - 10 wks                     |

### Applications

- Cabinets and enclosures
- Domestic appliances
- Bus chassis
- Solar energy
- Construction
- Heating, ventilation and air conditioning

### Installation Tools

#### Battery-Powered Tools

- PB2500
- PB2500 Smart
- PB3400



#### Hydro-Pneumatic Power Tools

- ProSet® XT range
- 7287



#### Lockbolt Tools

- 734 AV™ Series

### Specifications

|              |                                  |
|--------------|----------------------------------|
| Sizes:       | 4.8 mm to 10 mm (3/16" to 3/8")  |
| Materials:   | Aluminum, Steel, Stainless Steel |
| Head Styles: | Protruding, Countersunk          |

#### Notes:

\* Monobolt Requires Special Nose Pieces

3/16" - 71210-16020

1/4" - 71220-16021