

Safety data sheet

Page: 1/16

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ARDROX 3140

UFI: 5QWT-38J9-M003-AVP4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: corrosion inhibitor

Not recommended use: Uses other than recommended

1.3. Details of the supplier of the safety data sheet

Company:

Chemetall Ltd.

Napier House, Auckland Park

Bletchley, MK1 1BU

Great Britain

+44 1908 649333

sds.global-chemetall@basf.com

1.4. Emergency telephone number

International emergency number:

Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Asp. Tox. 1	H304 May be fatal if swallowed and enters airways.
STOT SE 3	H336 May cause drowsiness or dizziness.
Flam. Liq. 3	H226 Flammable liquid and vapour.

For the classifications not written out in full in this section the full text can be found in section 16.

2.2. Label elements

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Pictogram:



Signal Word:

Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P271	Use only outdoors or in a well-ventilated area.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P242	Use only non-sparking tools.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P243	Take action to prevent static discharges.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary Statements (Response):

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

P312	Call a POISON CENTER or physician if you feel unwell.
P370 + P378	In case of fire: Use water spray for extinction.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or physician.
P303 + P361 + P353	IF ON SKIN (or hair): Remove or Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P331	Do NOT induce vomiting.

Precautionary Statements (Storage):

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary Statements (Disposal):

P501	Dispose of contents and container to hazardous or special waste collection point.
------	---

Labeling of special preparations (GHS):

EUH066: Repeated exposure may cause skin dryness or cracking. Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Hazard determining component(s) for labelling: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics, Distillates (petroleum), hydrotreated heavy paraffinic, Distillates (petroleum), solvent-dewaxed heavy paraffinic, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatic

2.3. Other hazards

According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

Product does not contain a substance above legal limits included in the list established in accordance with Article 59(1) of Regulation (EC) No 1907/2006 for having endocrine disrupting properties or is identified to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

3.2. Mixtures

Chemical nature

organic compounds

Hazardous ingredients (GHS)

| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatic

Content (W/W): $\geq 30\%$ - $< 50\%$	Asp. Tox. 1
CAS Number: 64742-48-9	Flam. Liq. 3
EC-Number: 919-857-5	STOT SE 3 (drowsiness and dizziness)
REACH registration number: 01-2119473851-33	H226, H304, H336

| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Content (W/W): $\geq 5\%$ - $< 7\%$	Asp. Tox. 1
CAS Number: 64742-48-9	Flam. Liq. 3
EC-Number: 919-857-5	STOT SE (Central nervous system) 3
REACH registration number: 01-2119463258-33	(drowsiness and dizziness) H226, H304, H336 EUH066

| Sulfonic acids, petroleum, sodium salts

Content (W/W): $\geq 3\%$ - $< 5\%$	Skin Corr./Irrit. 2
CAS Number: 68608-26-4	Eye Dam./Irrit. 2
EC-Number: 271-781-5	H319, H315

| Distillates (petroleum), hydrotreated heavy paraffinic

Content (W/W): $\geq 1\%$ - $< 2\%$	Asp. Tox. 1
CAS Number: 64742-54-7	H304
EC-Number: 265-157-1	

| Distillates (petroleum), solvent-dewaxed heavy paraffinic

Content (W/W): $\geq 1\%$ - $< 2\%$	Asp. Tox. 1
CAS Number: 64742-65-0	H304
EC-Number: 265-169-7	

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Keep warm, calm and covered up. Immediately remove contaminated clothing. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

If inhaled:

Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

On skin contact:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

On contact with eyes:

If symptoms persist, seek medical advice. Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution.

On ingestion:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: aspiration pneumonia, dazed state, dizziness, Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Hazards: If swallowed, in the event of vomiting, risk of product entering the lungs. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment (decontamination, vital functions).

Antidote: No known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

5.2. Special hazards arising from the substance or mixture

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

Advice: Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

5.3. Advice for fire-fighters

Special protective equipment:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephtalate (PET), Polypropylene (PP), Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

Storage stability:

Storage temperature: 15 - 30 °C

Storage duration: 36 Months

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

No occupational exposure limits known.

Biological limit values (BLV)

No data available.

Components with PNEC

64742-54-7: Distillates (petroleum), hydrotreated heavy paraffinic

freshwater:

No PNEC value available.

marine water:

No PNEC value available.

intermittent release:

No PNEC value available.

STP:

No PNEC value available.

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

sediment (freshwater):
No PNEC value available.
sediment (marine water):
No PNEC value available.
soil:
No PNEC value available.
oral (secondary poisoning): 9.33 mg/kg

64742-65-0: Distillates (petroleum), solvent-dewaxed heavy paraffinic
oral (secondary poisoning): 9.33 mg/kg

Components with DNEL

64742-48-9: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics
worker: Long-term exposure- systemic effects, dermal: 208 mg/kg bw/day
worker: Long-term exposure- systemic effects, Inhalation: 871 mg/m³

64742-54-7: Distillates (petroleum), hydrotreated heavy paraffinic
worker: Long-term exposure- systemic effects, Inhalation: 2.73 mg/m³
worker: Long-term exposure - local effects, Inhalation: 5.58 mg/m³
worker: Long-term exposure- systemic effects, dermal: 0.97 mg/kg
consumer: Long-term exposure- systemic effects, oral: 0.74 mg/kg

8.2. Exposure controls

Appropriate engineering controls

If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. This can be achieved by the use of local exhaust ventilation and good general extraction. Ensure adequate ventilation.

Personal protective equipment

Respiratory protection:

Respiratory protection required if exposure limit (if available) may be exceeded (Gas filter EN 14387 A)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1)

nitrile rubber (NBR) - 0.4 mm coating thickness

The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

General safety and hygiene measures

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

Environmental exposure controls

For information regarding environmental exposure controls, see Section 6.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form:	liquid	
Colour:	brown	
Odour:	of hydrocarbons	
pH value:		
	substance/mixture is non-soluble (in water)	
Melting point:	not determined	
onset of boiling:	> 155 °C	
Flash point:	45 °C	
Flammability:	Flammable liquid and vapour.	
Lower explosion limit:	not determined	
Ignition temperature:	not determined	
Vapour pressure:	(20 °C) not determined	
	(50 °C) not determined	
Density:	0.860 g/cm ³ (20 °C)	(DIN 51757)
Solubility in water:	practically insoluble	
Viscosity, kinematic:	(40 °C) not determined	
Explosion hazard:	not explosive	
Fire promoting properties:	not fire-propagating	

9.2. Other information

Self heating ability: It is not a substance capable of spontaneous heating.

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

Germ cell mutagenicity

Assessment of mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity:

Based on available data, the classification criteria are not met.

Developmental toxicity

Assessment of teratogenicity:

Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Based on available data, the classification criteria are not met.

Aspiration hazard

May also damage the lung at swallowing (aspiration hazard).

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. The mixture has been assessed following regulation (EC) No 1272/2008 and is not classified as dangerous for the environment.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H₂O):

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

No data available concerning biodegradation and elimination.

12.3. Bioaccumulative potential

Bioaccumulation potential:

No data available.

12.4. Mobility in soil

Assessment transport between environmental compartments:

Adsorption in soil: No data available.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Do not discharge into drains/surface waters/groundwater.

Observe national and local legal requirements.

Dispose of the substance/product as special waste in accordance with Directive 2008/98/EC.

Waste key:

Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging:

Containers which are not properly emptied must be disposed pursuant to Directive 2008/98/EC

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14: Transport Information

Land transport

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

ADR

UN number or ID number: UN3295
UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S. (contains Naptha (Petroleum), hydrotreated heavy)
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for user: Tunnel code: D/E

RID

UN number or ID number: UN3295
UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S. (contains Naptha (Petroleum), hydrotreated heavy)
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for user:

Inland waterway transport

ADN

UN number or ID number: UN3295
UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S. (contains Naptha (Petroleum), hydrotreated heavy)
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no
Special precautions for user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

UN number or ID number: UN 3295
UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S. (contains Naptha (Petroleum), hydrotreated heavy)
Transport hazard class(es): 3
Packing group: III
Environmental hazards: no

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

Marine pollutant: NO

Special precautions for user:

Air transport

IATA/ICAO

UN number or ID number: UN 3295

UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S. (contains Naptha (Petroleum), hydrotreated heavy)

Transport hazard class(es): 3

Packing group: III

Environmental hazards: No Mark as dangerous for the environment is needed

Special precautions for user:

14.1. UN number or ID number

See corresponding entries for "UN number or ID number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Maritime transport in bulk according to IMO instruments

Maritime transport in bulk is not intended.

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2010/75/EU of the European Parliament and of the Council of 24 November 2010 on industrial emissions (integrated pollution prevention and control)

VOC content: 387.0 g/l

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 28, 3, 40, 75

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU):
Listed in above regulation: Flammable liquids, Categories 2 or 3 not covered by P5a and P5b

If other regulatory information applies that is not already provided elsewhere in this safety data sheet, then it is described in this subsection.

15.2. Chemical Safety Assessment

Chemical Safety Assessment not required

SECTION 16: Other Information

Restricted to professional users.

Literature and Data Sources: REACH-Regulation (EC) No. 1907/2006. CLP-Regulation (EC) No. 1272/2008.

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned in section 2 or 3:

Asp. Tox.	Aspiration hazard
STOT SE	Specific target organ toxicity — single exposure
Flam. Liq.	Flammable liquids
Skin Corr./Irrit.	Skin corrosion/irritation
Eye Dam./Irrit.	Serious eye damage/eye irritation
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
EUH066	Repeated exposure may cause skin dryness or cracking.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract

Chemetall (now part of BASF Group) Safety data sheet according to Regulation UK SI 2019/758 and UK SI 2020/1577 as amended from time to time.

Date / Revised: 07.09.2022

Version: 4.0

Date previous version: 15.09.2020

Previous version: 3.0

Date / First version: 26.11.2018

Product: **ARDROX 3140**

(ID no. 30706299/SDS_GEN_GB/EN)

Date of print 18.02.2023

Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships. NEN = Dutch Norm. NOEC = No Observed Effect Concentration. OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.

Vertical lines in the left hand margin indicate an amendment from the previous version.