

## PRODUCT DESCRIPTION

<b>Technology</b>	
<b>Cure</b>	
<b>Application</b>	

## GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Safety Data Sheet (SDS).

## TYPICAL PROPERTIES OF UNCURED MATERIAL

Directions For Use:

For Pre-assembled

## TYPICAL CURING PERFORMANCE

Cure Speed vs. Temperature

For Through Holes,

## TYPICAL PERFORMANCE OF CURED MATERIAL

Adhesive Properties

For Porosity Sealing

---

**For Disassembly**

**Note:**

**Clean-up**

**Storage**

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

**Optimal Storage: 8 °C to 21 °C. Storage below 8 °C or greater than 28 °C can adversely affect product properties**

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

**Product Specification**

In case products are delivered by Henkel Corporation or Henkel Canada, Inc. the following disclaimer is applicable:

**Approval and Certificate**

**Data Ranges**

Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.

**Conversions**

**Trademark usage**

**Disclaimer**

