

Roto Inject Fluid NDURANCE

Ultimate Mineral oil for your GA/GX compressor

Atlas Copco Roto Inject Fluid NDURANCE is a mineral based oil specially formulated to protect your GA-GX rotary screw compressor.



With several years of experience on developing cutting edge technology on compressors, Atlas Copco has designed a unique additive package that enables the Roto Inject Fluid NDURANCE to work in harmony with all other components in the compressor.

With extended service intervals of up to 4 000 hours when operating in mild conditions, RIF NDURANCE is a combination of a premium mineral base fluid with an enhanced additive package to allow your compressor to operate in dusty and humid conditions and keeping your system deposit free. The tailor made viscosity (55mm²/s) together with specially designed anti-wear additives provides your compressor the right lubrication for rotors, bearings and gears for a wide spread of operating conditions.



	Features	Benefits
High resistance against oxidation	Resistance against heavy pollution, high operating temperatures and high humidity.	Protects the compressor against oxidation, leading to a longer drain interval: up to 4 000 h or 1 year in mild ambient conditions.
Perfect sealing and anti-wear properties	Anti-wear additives are developed to protect the rotating parts. This will also help seal the gaps between the rotors when the air is in the compression phase.	Constant oil film protects the rotors and bearings during operation, preventing metal-metal contact of critical parts. Will avoid air leakages in the element.

Protection against corrosion, oxidation, wear, and deposits. 0.892 0 Td3Tw0.252 iTc 0 Tw ()Tj 0.yTj 0.985 0 Td4(o)T



Roto Inject Fluid NDURANCE

Lubricant characteristics

Appearance:

Colorless to straw pale yellow, transparent

Performance	Method	Unit	Value
Density at 15°C	ISO 3675	kg/dm ³	0,87
Viscosity at 40°C	ASTM D 445	mm ² /s	55
Viscosity index	ASTM D 2270		106
Foam stability	ASTM D 892	ml	0/0/0
Total acid number	ASTM D 974	mg KOH/g	0,1
FZG fail stage	ISO 14635-2		11
Rust test	ASTM D 665B		Pass
Pour point	ASTM D 97	°C	-33

These characteristics are typical of current production. Whilst future production will be conform to Atlas Copco’s specification, variations in these characteristics may occur. Complies with ISO 6743 /3 /1A class L-DAH

ID Card

Name	Roto Inject Fluid NDURANCE
Oil type	Mineral based lubricant
Service intervals	4 000 h or 1 year at mild ambient conditions
Mild ambient conditions	Ambient temperature range from 0°C to +30°C and dusty environment or ambient temperature range from 0°C to +30°C and humid environment
	Maximum operating pressure 13 bar
Equipment	Atlas Copco single stage oil-injected screws
Compatibility	GA - GX compressors
Capacity (ID)	5 l plastic can (1630 1146 00) 20 l plastic can (1630 0918 00) 209 l metal drum (1630 0919 00) 1000 l container (1630 1442 00)



2935 0046 22 © Atlas Copco Airpower n.v., Belgium, November 2019 - subject to alteration without prior notice.

