



SAFETY DATA SHEET

Version #: 1,0
Issue date: 23-January-2023
Revision date: 23-January-2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture AMS4 SILICONE GREASE

Registration number -

Synonyms None.

Product code UDS000078AE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricants

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries UK Ltd.

Address Wylds Road
Castlefield Industrial Estate
TA6 4DD Bridgwater Somerset
United Kingdom

Telephone +44 1278 727200

Fax +44 1278 425644

E-mail hse.uk@crcind.com

Website www.crcind.com

Company name CRC Industries Europe bv

Address Touwslagerstraat 1
9240 Zele
Belgium

Telephone +32(0)52/45.60.11

Fax +32(0)52/45.00.34

E-mail hse@crcind.com

Website www.crcind.com

1.4. Emergency telephone number Tel.:(+44)(0)1278 72 7200 (office hours: 9-17h GMT)

Austria National Poisons Information Centre +431 406 4343 (Available 24 hours a day.)

Belgium National Poisons Control Center 070 245 245 (Available 24 hours a day.)

Bulgaria National Toxicological Information Centre +359 2 9154233 (Available 24 hours a day.)

Czech Republic National Poisons Information Centre +420 224 919 293, or +420 224 915 402 (Hours of operation not provided.)

Denmark National Poisons Control Center +45 82 12 12 12 (Available 24 hours a day.)

Estonia National Poisons Information Centre 16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays))

Finland National Poison Information Center	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day.)
France National Poisons Control Center	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day.)
Hungary National Emergency Phone Number	36 80 20 11 99 (Available 24 hours a day.)
Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided.)
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided.)
Netherlands National Poisons Information Center (NVIC)	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)
Norway Norwegian Poison Information Center	22 59 13 00 (Available 24 hours a day.)
Portugal Poison Centre	800 250 250 (Available 24 hours a day.)
Romania Număr de telefon care poate fi apelat în caz de urgență:	021 5992300, int. 291 Spitalul Clinic de Urgență București: spital@urgentafloreasca.ro
Romania	0265 212111, 0265 211292, 0265 217235 Spitalul Clinic Județean de Urgență Târgu Mureș: secretariat@spitjudms.ro
Slovakia National Toxicological Information Centre	+421 2 5477 4166 (Available 24 hours a day.)
Sweden National Poison Information Center	112 - and ask for Poison Information (Available 24 hours a day.)
Switzerland Tox Info Suisse	145 (Available 24 hours a day.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols

Category 1

H222 - Extremely flammable aerosol.

H229 - Pressurized container: May burst if heated.

Health hazards

Skin corrosion/irritation

Category 2

H315 - Causes skin irritation.

Serious eye damage/eye irritation

Category 2

H319 - Causes serious eye irritation.

Specific target organ toxicity - single exposure

Category 3 narcotic effects

H336 - May cause drowsiness or dizziness.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard

Category 2

H411 - Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:

Hydrocarbons, C7-C8, cyclics, Propan-2-ol; Isopropyl alcohol; Isopropanol

Hazard pictograms



Signal word

Danger

Hazard statements

H222

Extremely flammable aerosol.

H229	Pressurized container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist/vapours.
P271	Use only outdoors or in a well-ventilated area.

Response

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C7-C8, cyclics	30 - 60	- 927-033-1	01-2119486992-20	-	
Classification: Flam. Liq. 2;H225, Skin Irrit. 2;H315, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					
Propan-2-ol; Isopropyl alcohol; Isopropanol	5 - 10	67-63-0 200-661-7	01-2119457558-25	603-117-00-0	
Classification: Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336					

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

5.1. Extinguishing media

Suitable extinguishing media

Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Special protective equipment for firefighters

Special fire fighting procedures

Specific methods

Extremely flammable aerosol.

Alcohol resistant foam. Powder. Carbon dioxide (CO₂).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001

Components

Type

Value

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

MAK

500 mg/m³

Austria. MAK List, OEL Ordinance (GwV), BGBI. II, no. 184/2001

Components	Type	Value
	STEL	200 ppm
		2000 mg/m3
		800 ppm

Belgium. Exposure Limit Values

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm
	TWA	500 mg/m3
		200 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3
	TWA	980 mg/m3

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	MAC	999 mg/m3
		400 ppm
	STEL	1250 mg/m3
		500 ppm

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	980 mg/m3
		400 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	Ceiling	1000 mg/m3
	TWA	500 mg/m3

Denmark. Exposure Limit Values

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TLV	490 mg/m3
		200 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
		250 ppm
	TWA	350 mg/m3
		150 ppm

Finland. Workplace Exposure Limits

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	620 mg/m3
	TWA	250 ppm
		500 mg/m3
		200 ppm

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	VLE	980 mg/m3
	Regulatory status:	Indicative limit (VL)
		400 ppm
	Regulatory status:	Indicative limit (VL)

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	500 mg/m3
		200 ppm

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	AGW	500 mg/m3
		200 ppm

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1225 mg/m3
		500 ppm
	TWA	980 mg/m3
		400 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		500 mg/m3
	TWA	500 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	490 mg/m3
		200 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	400 ppm
		200 ppm
	TWA	200 ppm

Italy. Occupational Exposure Limits

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
	TWA	350 mg/m3

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
		250 ppm
	TWA	350 mg/m3
		150 ppm

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TLV	245 mg/m3
		100 ppm

Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1200 mg/m3
	TWA	900 mg/m3

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	500 mg/m3
		203 ppm
	TWA	200 mg/m3
		81 ppm

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm
	TWA	500 mg/m3
		200 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	TWA	500 mg/m3
		200 ppm

Spain. Occupational Exposure Limits

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm
	TWA	500 mg/m3
		200 ppm

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	600 mg/m3
		250 ppm
	TWA	350 mg/m3
		150 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1000 mg/m3
		400 ppm
	TWA	500 mg/m3
		200 ppm

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	STEL	1250 mg/m3
		500 ppm
	TWA	999 mg/m3
		400 ppm

Biological limit values

Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	50 mg/l	Acetone	Urine	*
	50 mg/l	Acetone	Blood	*
	0,86 umol/l	Acetone	Urine	*
	0,86 umol/l	Acetone	Blood	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	25 mg/l	ACETON	Urine	*
	25 mg/l	ACETON	Blood	*

* - For sampling details, please see the source document.

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	430 µmol/l 25 mg/l	Acetone	Urine	*
		Acetone	Urine	*

* - For sampling details, please see the source document.

Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	40 mg/l	Acetona	Urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	25 mg/l	ACETON	Urine	*
	25 mg/l	ACETON	Blood	*

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General population

Components	Value	Assessment factor	Notes
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Long-term, Systemic, Dermal	319 mg/kg bw/day	2	Repeated dose toxicity
Long-term, Systemic, Inhalation	89 mg/m3	2	Repeated dose toxicity
Long-term, Systemic, Oral	26 mg/kg bw/day	2	Repeated dose toxicity

Workers

Components	Value	Assessment factor	Notes
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Long-term, Systemic, Dermal	888 mg/kg bw/day	1	
Long-term, Systemic, Inhalation	500 mg/m3	1	

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Freshwater	140,9 mg/l	1	
Secondary poisoning	160 mg/kg	30	Oral
Sediment (freshwater)	552 mg/kg		
Soil	28 mg/kg		

Exposure guidelines

Cyprus OEL: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Can be absorbed through the skin.

Hungary OELs: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Can be absorbed through the skin.

Iceland OELs: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Can be absorbed through the skin.

Ireland Exposure Limit Values: Skin designation

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.
Skin protection	
- Hand protection	When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended. Suitable gloves can be recommended by the glove supplier.
- Other	Wear appropriate chemical resistant clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type A)
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Aerosol.
Colour	Off-white.
Odour	Solvent.
Melting point/freezing point	Not available.
Boiling point or initial boiling point and boiling range	101 °C (213,8 °F)
Flammability	Not available.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	1,2 %
Explosive limit – upper (%)	9,4 %
Flash point	-6,0 °C (21,2 °F)
Auto-ignition temperature	258 °C (496,4 °F)
Decomposition temperature	Not available.
pH	Not applicable.
Kinematic viscosity	Not available.
Solubility	
Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water) (log value)	Not available.
Vapour pressure	Not available.
Density and/or relative density	
Relative density	0,81 g/cm3 20 °C
Vapour density	Not available.
Particle characteristics	Not available.
9.2. Other information	
9.2.1. Information with regard to physical hazard classes	No relevant additional information available.
9.2.2. Other safety characteristics	
Aerosol spray enclosed space	
Deflagration density	Not available.
Aerosol spray ignition distance	Not available.

Evaporation rate Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Acids. Strong oxidising agents. Chlorine. Isocyanates.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components	Species	Test Results
-------------------	----------------	---------------------

Hydrocarbons, C7-C8, cyclics

Acute

Dermal

LD50 Rat 2920 mg/kg

Inhalation

LC50 Rat 23300 mg/m³

Oral

LD50 Rat 5840 mg/kg

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Acute

Inhalation

LC50 Rat > 25000 mg/m³, 6 h

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory sensitisation Based on available data, the classification criteria are not met.

Skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Mixture versus substance information

Not available.

11.2. Information on other hazards

Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Other information	Not available.

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
Hydrocarbons, C7-C8, cyclics		
Acute		
Other	IC50	Pseudokirchnerella subcapitata 10 mg/l, 72 hours
Aquatic		
Acute		
Crustacea	EC50	Daphnia magna 3 mg/l, 48 hours
Fish	LC50	Rainbow trout 3,6 mg/l, 96 hours
Chronic		
Crustacea		Daphnia magna 1 mg/l, 21 days
Fish		Rainbow trout 0,84 mg/l, 28 days
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)		
Aquatic		
Acute		
Crustacea	LC50	Brine shrimp (Artemia salina) > 10000 mg/l, 24 hours
Fish	LC50	Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours

12.2. Persistence and degradability**12.3. Bioaccumulative potential****Partition coefficient****n-octanol/water (log Kow)**

Propan-2-ol; Isopropyl alcohol; Isopropanol 0,05

Bioconcentration factor (BCF)

Not available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. GWP: 2

12.8. Additional information**Estonia Dangerous substances in soil Data**

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)	Chemical pesticides (As the total sum of the active substances) 0,5 mg/kg
	Chemical pesticides (As the total sum of the active substances) 20 mg/kg
	Chemical pesticides (As the total sum of the active substances) 5 mg/kg

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Residual waste**

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	Not assigned.
Label(s)	2.1
Hazard No. (ADR)	Not assigned.
Tunnel restriction code	D
ADR/RID - Classification code:	5F
14.4. Packing group	Not assigned.
14.5. Environmental hazards	Yes
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA


14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	Not assigned.
14.4. Packing group	Not assigned.
14.5. Environmental hazards	Yes
ERG Code	10L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

14.1. UN number	UN1950
14.2. UN proper shipping name	Aerosols, flammable, Marine pollutant
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	Not assigned.
14.4. Packing group	Not assigned.
14.5. Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
14.7. Maritime transport in bulk according to IMO instruments	Not established.



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.
AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).
ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).
CAS: Chemical Abstract Service.
Ceiling: Short Term Exposure Limit Ceiling value.
CEN: European Committee for Standardization.
CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.
GWP: Global Warming Potential.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG: International Maritime Dangerous Goods.
MAC: Maximum Allowed Concentration.
MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).
MARPOL: International Convention for the Prevention of Pollution from Ships.
PBT: Persistent, bioaccumulative and toxic.
REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).
RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
STEL: Short term exposure limit.
TLV: Threshold Limit Value.
TWA: Time Weighted Average.
VLE: Exposure Limit Value.
VME: Exposure Average Value.
VOC: Volatile organic compounds.
vPvB: Very persistent and very bioaccumulative.
STEL: Short-term Exposure Limit.

References

Information on evaluation method leading to the classification of mixture

Not available.

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

CRC Industries Europe UK Limited cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.